

Appln. No. 09/511,408
Amdt. dated January 27, 2004
Reply to Office Action of October 27, 2003

PATENT

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1. (Currently amended) An electronic camera apparatus with the capability of correcting luminance balance in an image signal for reading out, read out from an image sensing element device, an said image signal representing which represents a color image constructed by a number plurality of pixels to which predetermined colors are assigned and has pieces of luminance information with analog values representing luminances of the pixels, the luminance information being discrete on a time axis, and generating a desired image from the image signal, comprising:

Al
a luminance correction section for generating coupled at the output of the image sensing element and operative, on individual units of raw colors of said pixels, each one of said pixels each being formed from a set of predetermined units of colors and each unit of color having an analog value representing luminance information, the luminance information being discrete on a time axis, to

- 1) generate individual correction coefficients for each of said predetermined colors of each said pixel from a plurality of correction coefficients in units of pixels, correcting
- 2) correct white balance using corresponding luminance information in the image signal on the basis of each said correction coefficient, and
- 3) output outputting a new image signal used for image generation.

2. (Currently amended) An apparatus according to claim 1, further comprising a wherein said luminance correction section is connected in series with the image signal.

3. (Original) An apparatus according to claim 1, wherein said luminance correction section comprises.

Appln. No. 09/511,408
Amdt. dated January 27, 2004
Reply to Office Action of October 27, 2003

PATENT

a correction control section for sequentially generating a luminance correction amount corresponding to each pixel from the plurality of correction coefficients on the basis of a clock signal synchronized with each luminance information in the image signal, and

a luminance correction amplification section for switching a gain in accordance with the luminance correction amount sequentially generated by said correction control section to amplify the input image signal by a gain corresponding to each luminance correction amount in units of luminance information, and outputting the new image signal.

4. (Original) An apparatus according to claim 1, wherein said luminance correction section comprises

Alt
a first correction control section for sequentially generating a luminance correction amount corresponding to each pixel from a plurality of first correction coefficients on the basis of a clock signal synchronized with each luminance information in the image signal,

a second correction control section for sequentially generating a luminance correction amount corresponding to each pixel from a plurality of second correction coefficients on the basis of a clock signal synchronized with each luminance information in the image signal, and

a luminance correction amplification section for setting a synthesized gain as a product of a first gain corresponding to the luminance correction amount sequentially generated by said first correction control section and the luminance correction amount sequentially generated by said second correction control section to amplify the input image signal by the synthesized gain corresponding to each luminance correction amount in units of luminance information, and outputting the new image signal.

5. (Original) An apparatus according to claim 1, wherein the plurality of correction coefficients are formed from luminance correction amounts in units of predetermined colors assigned to the pixels, and

said luminance correction section sequentially selects and uses the luminance correction amounts corresponding to the colors assigned to the pixels as the individual correction coefficients in units of pixels.

Appl. No. 09/511,408
Amdt. dated January 27, 2004
Reply to Office Action of October 27, 2003

PATENT

6. (Original) An apparatus according to claim 1, wherein the plurality of correction coefficients are formed from luminance correction amounts corresponding to coordinate positions defined by two-dimensional coordinates on the color image, and
said luminance correction section sequentially selects and uses the luminance correction amounts corresponding to the coordinate positions of the pixels as the individual correction coefficients in units of pixels.

7. (Original) An apparatus according to claim 1, wherein the plurality of correction coefficients are formed from luminance correction amounts corresponding to coordinate regions defined by two-dimensional coordinates on the color image, and
said luminance correction section sequentially selects and uses the luminance correction amounts corresponding to the coordinate regions to which the pixels belong as the individual correction coefficients in units of pixels.

8. (Original) An apparatus according to claim 1, wherein the plurality of correction coefficients are formed from axial luminance correction amounts representing two correction distribution characteristics changing in axial directions of two coordinate axes that form two-dimensional coordinates set on the color image, and
said luminance correction section refers to corresponding axial luminance correction amounts in units of coordinate axes on the basis of coordinate positions of the pixels and sequentially generates the luminance correction amounts corresponding to the pixels from two obtained axial luminance correction values.

9. (Original) An apparatus according to claim 1, wherein the plurality of correction coefficients are formed from axial luminance correction amounts representing two correction distribution characteristics changing in axial directions of two coordinate axes that form two-dimensional coordinates set on the color image, and
said luminance correction section refers to corresponding axial luminance correction amounts in units of coordinate axes on the basis of coordinate positions of the pixels and sequentially generates and uses products of two obtained axial luminance correction values as the luminance correction amounts corresponding to the pixels.

Appln. No. 09/511,408
Amdt. dated January 27, 2004
Reply to Office Action of October 27, 2003

PATENT

10. (Original) An apparatus according to claim 1, wherein the plurality of correction coefficients are formed from axial luminance correction amounts representing two correction distribution characteristics changing in axial directions of two coordinate axes that form two-dimensional coordinates set on the color image, and

said luminance correction section refers to corresponding axial luminance correction amounts in units of coordinate axes on the basis of coordinate positions of the pixels and sequentially generates and uses sums of two obtained axial luminance correction values as the luminance correction amounts corresponding to the pixels.
